Hardwa	re Kit (rowing version, two stations)			
QTY	ITEM		USE	UOM
50	1/4" Classic Filament 3-strand Polyester Line		painter and foot rests	ft
2	Armstrong 6" deck plate Round Cream		tank compartment access plates	ea
1	Gaco oarlock pair for 1/2" sockets	(A)	horn oarlocks for solo rowing (2nd pair add'l)	pair
1	Gaco Oarlock pair including 4 sockets	TP	can get another set of top mount for solo station	pack
12	Heading twine, Gold		lanyards for oarlocks	ft
1	Br strap eye 5/16" pair (#8 fastener)	of PO	bow eye (screw), tie down	pr
2	SB wood screw #8 x 3/4 FH slot	Normal Street	bow eye strap (not for towing)	ea
8	SS #8 x 1" OH wood screw (slot)		oarlocks (top)	ea
4	Brass wood screw FH slot 10x 1-3/4"		forward fixed seat	ea
4	Brass finish washer #8	6	bow seat fixed	ea
2	1/4"-20 x 1.5" partially threaded SS thumb screws	2	moveable seat	ea
4	Brass tapping inserts for hardwood, 1/4-20		seat riser threaded inserts	ea
6	Brz half-oval 3/8" predrilled and c-sunk	• • • • •	Skeg - 38" (bend 32" from bow end), Bow 34" (bend 12" from eye), 91"+11" (optional keel,stem length)	ft
1	SB wood screw #4 x 1/2 FH slot	-	half oval screws	bx
26	tapping screw S/S FH sqdr #8x1-1/4"		Rubrails at bow and stern (8), side arms to bottom frame (6 per frame), transom to knees (4), skeg (2)	ea
2	tapping screw S/S FH sqdr #8x 2"	and the second se	skeg from inside boat	ea
1	Elastomeric marine sealant 3oz tube clr		bedding hardware	ft
2	Packing fee			ea
Upgrade	95			
1	Edge mount oarlock socket Br (#10 screws)		for tandem rowing position	pack
4	1/4" x 7/8" QR pin 18-8 SS		adjustable foot rest	ea
2	6063 Aluminum U-channel, 2-ft length		adjustable foot stretcher, needs drilling	ft